


1700

SEMI-CIRCULAR FLOAT VALVES

Inverted Vent Check Valves protect tanks and bulkheads from pressure build-up during loading and unloading of liquid or dry cargo and assure maximum efficiency during operations. The ball float prevents contamination of the tank cargo by sea water during heavy seas. All steel castings are hot dipped galvanized. All aluminum castings are anodized.



BODY



FLOAT



FLAME SCREEN
AND SPACER



PROTECTIVE
MESH



CAP



SPECIFICATIONS

GALVANIZED STEEL

FLOAT MATERIAL:

- STAINLESS STEEL
- COPPER (STANDARD)
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- BUTTWELD
- SOCKETWELD
- FLANGED

SIZES:

- 5", 6", 8", 10", 12", 14", 16"

BRONZE

FLOAT MATERIAL:

- STAINLESS STEEL
- COPPER (STANDARD)
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- FLANGED
- SIL-BRAZED

SIZES:

- 5", 6", 8", 10", 12"

STAINLESS STEEL

FLOAT MATERIAL:

- STAINLESS STEEL
- COPPER (STANDARD)
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- BUTTWELD
- SOCKETWELD
- FLANGED

SIZES:

- 5", 6", 8", 10", 12", 14", 16"

ANODIZED ALUMINUM

FLOAT MATERIAL:

- STAINLESS STEEL (STANDARD)
- COPPER
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- BUTTWELD
- SOCKETWELD
- FLANGED

SIZES:

- 5", 6", 8", 10", 12"

ABS TYPE APPROVED



WAGER
COMPANY

WWW.WAGERUSA.COM
Toll Free USA: 800-562-7024